



Číslo položky	Průměr [mm]	Délka [m]	Počet [ks]	Celkem [m]		
				ØR8	ØR10	ØR12
1	R12	4,700	9			42,30
2	R12	5,100	9			45,90
3	R12	2,490	9			22,41
4	R12	6,300	9			56,70
5	R12	5,090	12			61,08
6	R12	3,790	9			34,11
7	R12	1,600	9			14,40
8	R8	3,680	7			
9	R8	1,150	50			
10	R8	1,200	10			
11	R8	0,980	9			
12	R8	1,180	12			
13	R10	95,000	1			
14	R8	1,060	11			
15	R10	1,500	2			
16	R12	1,500	3			
17	R8	1,060	26			
18	R8	0,840	18			
19	R8	80,000	1			
20	R8	1,400	6			
21	R8	1,050	2			
22	R8	1,840	2			
				m'		
				kg/m'		
				kg		
				kg		
				415,7		

BETON C 25/30 XC1
OCEL B500B
KRYTÍ 25 MM

POZNÁMKA

PRO OSAZENÍ VÝZTUŽE JE NUTNO POUŽÍT DISTANČNÍ PODLOŽKY A PODPORY HORNÍ VÝZTUŽE TAK, ABY BYLA ZACHOVÁNA POLOHA VÝZTUŽE A JEJÍ KRYTÍ.