

3NP - 1 ks

	m2 / PRVEK	m2 CELKEM
nátěrová plocha	147,07	147,07

POL.	PROFIL	DĚLKA [mm]	ŠÍŘKA [mm]	KS / PRVEK	KS CEL.	kg/bm (kg/m2)	kg / PRVEK	kg CELKEM
0	I 180	2 750		2	2	21,900	120,45	120,45
0	U 180 (2-krab.)	11 400		1	1	44,000	501,60	501,60
0	TR4HR 150/100/6,3	3 600		1	1	23,300	83,88	83,88
0	TR4HR 150/6,3	4 800		1	1	28,300	135,84	135,84
0	TR4HR 150/6,3	19 700		1	1	28,300	557,51	557,51
0	U 180 (2-krab.)	19 400		1	1	44,000	853,60	853,60
0	TR4HR 150/100/6,3	19 700		1	1	23,300	459,01	459,01
0	TR4HR 150/100/6,3	3 850		1	1	23,300	89,71	89,71
0	TR4HR 100/4	10 650		1	1	11,850	126,20	126,20
0	TR4HR 150/100/6,3	3 650		1	1	23,300	85,05	85,05
0	TR4HR 100/4	4 650		2	2	11,850	110,21	110,21
0	TR4HR 100/4	4 200		1	1	11,850	49,77	49,77
0	TR4HR 100/4	4 450		2	2	11,850	105,47	105,47
0	HE200B	950		2	2	63,000	119,70	119,70
0	HE200B	600		4	4	63,000	151,20	151,20
0	HE200B	4 300		6	6	63,000	1 625,40	1 625,40
0	HE200B	8 000		3	3	63,000	1 512,00	1 512,00
0	HE200B	6 000		2	2	63,000	756,00	756,00
0	HE200B	2 850		1	1	63,000	179,55	179,55
0	TR4HR 150/100/6,3	250		5	5	23,300	29,13	29,13
0	TR4HR 60/4	500		5	5	7,100	17,75	17,75
HMOTNOST 1 ks 3NP							7 669,01	
HMOTNOST 1 ks 3NP								7 669,01

OCEL DLE VÝKAZU

11 626 KG

DETAILY 10%

1 163 KG

CELKEM OCELI S235**12 789 KG****Prořez si určí dodavatel**